

## Wood burning heater Harvia Legend 240 SL black

WKLE20SLM

*The Harvia Legend wood burning heaters give you the ultimate sauna experience. The black steel frame has a mighty amount of stones inside, and as they heat up, you get a magnificent sauna bath even at a lower temperature. The large number of stones ensures good heat, even if the fire dies down in between.*



### Features

Main material : Steel

H x W x D : 830.0 x 600.0 x 780.0 mm

Net weight (kg) : 81.7

Stone amount (kg) : 200.0

ID	GTIN	Power	Sauna room size min - max m3
WKLE20SLM	6417659036504	21 kW	10.0-24.0

## Spare parts

Product	ID	Pcs
Ashpan ES/SL	Z2ES-125	
Furnace grate	ZKIP-10	
Connection pipe	ZKIP-130	
Hinge pin	ZKIP-50	
Legend 240 SL/Duo steel frame	WX503	
Stove body 20 SL	ZROST-300SL	
Handle for stove + screws	ZKIP-670	
Handle and screws, Chrome	SPZKIP-670	1
Adjustable legs for LG150/SL	SPZKIP-918	
Hinge pin	SPZKIP-50	1
Door for stove with knob, black	SP010	
Fire chamber side plates Legend 240/300	SP525	1
Glass 184x210x4 mm Stoves 2006-, transparent	SPZTS-36	
Stove door with glass (from 2006)	SP048	
Cast-iron grating 135x290mm, sauna heaters	SPZKIP-10	1
Ash box, 20 ES/SL,ESGF	SP681	
Cap for smoke hole (Ø 75 mm)	SPZROB-430	1

## Technical details

Technical data	Type / attribute	WKLE20SLM
	Color	Black
	Power output	21 kW
	Stone sizes	Ø10–15 cm
	Stone amount (kg)	200
Dimensions	Product width	600
	Product height	830
	Product depth (mm)	780
	Net weight (kg)	81.7
	Gross weight	85.4
	Package width	810
	Package height	850
	Package depth	620
Connections	Flue connection locations	Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	630
	Safety distance front (combustible materials)	630
	Safety distance right side (combustible materials)	200
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	200
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	250
	Safety distance (Ceiling)	1000
Room min. height(depends on connections and therefore from output, star/delta)	1850	

## Technical details

Technical data	Type / attribute	WKLE20SLM
	Installation opening height	1850
	Installation opening width	1000
	Installation opening depth	1660